

## WATERPROOF 48 - WATERPROOF DEVICES

## DESCRIPTION



- Products in technical thermoplastic - resistant material, non-conductive.
- White (RAL 9003).
- Grey (RAL 7035).

## CHARACTERISTICS

- Mechanisms in technical thermoplastic - resistant material, non-conductive.
- High resistance against impacts and against elements (IK07 and IP65).
- Control Devices
  - 16A - 250V~ - Connections with screw terminals. It allows the usage of rigid and flexible cable.
  - Pilot Light.
  - In accordance with EN 60669-1 Standard, tested according to 19.3:

| Relationship between rated current of the switch and rated power of the SBL circuit |                                    |
|---|------------------------------------|
| Rated current of the switch, $I_n$ [A]  | Rated power of the SBL circuit [W] |
| $I_n \leq 10$   | 100                                |
| $10 < I_n \leq 13$  | 150                                |
| $13 < I_n \leq 16$  | 200                                |
| $16 < I_n \leq 20$  | 250                                |

SBL - Self Ballasted Lamp (CFL or LED)

## ■ Energy Sockets


- Earth Socket (Schuko and French types):
  - 16A - 250V~.
  - Connections with screw terminals.
  - In accordance with IEC 60884-1; DIN VDE 0620-1 (Schuko) and NF C 61-314 (French) Standards.
  - Energy Sockets: Singles, Double Vertical and Horizontal.

■ **Variety of Functions:** Control Devices, Electrical Blinds Control, Energy Sockets, etc...

■ Possibility of double vertical combination (Ref. 48995 A) or horizontal combination (Ref. 48994 A) with resource of Double Bases.

■ Adaptation of functions of **QUADRO 45** by using the 48 Series Box with Cover for QUADRO 45 Series (Ref. 48998 C).

■ **Draining Holes:** All the products of the **Waterproof 48 Series** have two pre-drilled draining holes. Depending on the mounting position of the product, the draining hole pointing to the lower part of the base must be open.



## DIMENSIONS (mm)

